

***Chengshan***



## CAR602



- Close shoulder design prevents irregular wear and improves mileage.
- Strengthened belt design improves crown stability.
- Unique pattern design improve block's rigidity, decreases block's slippage in driving and promotes even wear.
- Special groove and sipe design strengthen handling performance and anti-hydroplaning performance.
- Diamond surface with strip shape design provides ride comfort and self-cleaning ability.
- Unique siping design improves grip and heat dispersion.

SIZE	PR	LI	SS	MEASURE RIM	TYPE	MAX LOAD (KG)		MAX LOAD (LBS)		MAX. INFLATION PRESSURE (KPa)		MAX. INFLATION PRESSURE (PSI)		DIMENSION (mm)		TREAD DEPTH (mm)	TREAD DEPTH 32nds
						SINGLE	DUAL	SINGLE	DUAL	SINGLE	DUAL	SINGLE	DUAL	Section width	O.D.		
11R22.5	16PR	146/143	L	8.25	TL	3000	6610	2725	6005	830	120	830	120	279	1054	14.5	19
11R24.5	16PR	149/146	L	8.25	TL	3250	7160	3000	6610	830	120	830	120	279	1104	14.5	19
215/75R17.5	16PR	135/133	L	6	TL	2180	4805	2060	4540	850	125	850	125	211	767	12	16
225/70R19.5	14PR	128/126	L	6.75	TL	1800	3970	1700	3750	760	760	760	110	226	811	12	16
245/70R19.5	16PR	136/134	M	7.5	TL	2240	4940	2120	4675	825	120	825	120	248	839	13	17
255/70R22.5	16PR	140/137	M	7.5	TL	2500	5510	2300	5070	830	120	830	120	255	930	13.5	17
295/75R22.5	16PR	146/143	L	9	TL	3000	6610	2725	6005	830	120	830	120	298	1014	14.5	19

## CST125



- Mixed pattern design offers excellent traction.
- Arc-shaped design of grooves bottom offers great anti-cracking performance.
- Stone-ejectors at the bottom of grooves improve tire self-cleaning ability and esthetic value.

SIZE	PR	LI	SS	MEASURE RIM	TYPE	MAX LOAD (KG)		MAX LOAD (LBS)		MAX. INFLATION PRESSURE (KPa)		MAX. INFLATION PRESSURE (PSI)		DIMENSION (mm)		TREAD DEPTH (mm)	TREAD DEPTH 32nds
						SINGLE	DUAL	SINGLE	DUAL	SINGLE	DUAL	SINGLE	DUAL	Section width	O.D.		
11R22.5	16PR	148/145	L	8.25	TL	3150	2900	6940	6390	850	850	125	125	279	1054	21.5	28
11R24.5	16PR	149/146	L	8.25	TL	3250	3000	7160	6610	830	830	120	120	279	1104	21.5	28

## CST326A



- Massive lugs provide the tire with excellent traction and driving performance.
- Deeper tread offers extended mileage for good economy.
- Open shoulder structure provide tire with good water dispersion as well as side slip resistance.

SIZE	PR	LI	SS	MEASURE RIM	TYPE	MAX LOAD (KG)		MAX LOAD (LBS)		MAX. INFLATION PRESSURE (KPa)		MAX. INFLATION PRESSURE (PSI)		DIMENSION (mm)		TREAD DEPTH (mm)	TREAD DEPTH 32nds
						SINGLE	DUAL	SINGLE	DUAL	SINGLE	DUAL	SINGLE	DUAL	Section width	O.D.		
11R22.5	16PR	146/143	J	8.25	TL	3000	2725	6610	6005	830	830	120	120	279	1054	18	23