

DURATION

CATÁLOGO DE PRODUCTO



DURATION



- Sound water-evacuation and skidding-resistance capability.
- Soundly resistance irregular wear.

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	PSI	KG	PSI			
11R22.5	146/143	M	15.0	7.50,8.25	2725	120	3000	120	279	1054	51.80
11R24.5	149/146	M	15.0	7.50,8.25	3000	120	3250	120	279	1104	55.60
295/75R22.5	146/143	M	15.0	8.25,9.00	3000	120	2725	120	298	1014	50.65



- Suitable for good road surface application.
- With excellent anti-side-skid character, low rolling resistance.
- Low heat generating, excellent high-speed driving character.

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	PSI	KG	PSI			
11R22.5	146/143	L	21.0	7.50,8.25	2725	120	3000	120	279	1065	54.60
11R24.5	149/146	L	21.0	7.50,8.25	3000	120	3250	120	279	1116	58.60
295/75R22.5	146/143	L	21.0	8.25,9.00	3000	120	2725	120	298	1020	52.80

DURATION



FM-71

•Sounds bearing, braking and driving capability.

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	PSI	KG	PSI			
11R22.5	146/143	M	15.0	7.50,8.25	2725	120	3000	120	279	1054	51.80
11R24.5	149/146	M	15.0	7.50,8.25	3000	120	3250	120	279	1104	55.60



FM-81

*•Suitable to transport on asphalt road or other bad road condition.
•Tyres with pattern have powerful grip ability, excellent traction character.*

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	PSI	KG	PSI			
11R22.5	146/143	J	23.0	8.25	2750	120	3000	120	279	1065	56.50
11R24.5	149/146	J	23.0	8.25	3000	120	3250	120	279	1116	69.50